## EQ-LK26

Interactive (Multi-Purpose)

Floor- Standing Kiosk







- ☑ Token Dispenser (Queue System)
- Patients / Customer Registration
- Customer Information & Promotion

## **EQ-LK25 - Floor Standing Kiosk**

TECHNICAL SPECIFICATIONS	
Display Size & Type	Standard -> 21.5" IPS LED – Commercial Grade (Also Available in 15.6" / 17.3" / 18.5" / 26" & 32" Screen Sizes)
Touch Screen	Multi-Touch High Transparence, High Precision & Durability (With Life Span of 10+ Years)
Orientation	Standard Layout> Portrait (Also available in Landscape)
Menu Options (Number of Services)	Single / Multi-Level Menu Options (up to 4000+) (Multiple Selection of Services with Auto-Transfer Facility)
Language / Interface	Multi-Lingual Touch-Interface (English / French / Spanish / Italian / German / Finnish / Dutch / Arabic / Tagalog / Amharic & more — up to 35 different languages)
Housing / Enclosure	Durable Metal Frame (In Any Required Color)  Moisture-Proof / Anti=Rust / Anti-Acid / Anti-Dust / Static-Free
СРИ	i3, i5, i7 or i9 (Windows) with 8GB / 1TB SSD (upgradeable) Quad / Octa-Core (Android) with 2GB / 16GB (upgradeable)
Token Printer	High Speed Thermal Printer with Auto-Cutter (55m or 80mm) (Also available with Deskjet & Laser Printer A3 / A4 / A5 - as required)
Barcode Printing	Supports All Types of Linear (2D), QR-Code & other 3D Barcodes
Token Printing Width	From 37mm to 80 mm
Token Printing Height	From 20mm to (Unlimited – depending upon the roll length)
Built-in Sub-Control	Integrated with EaZy-Q Main Control System
Other Interface/Peripherals (Optional)	Numeric-Keypad / Anti-Vandal-Keyboard / Camera / IR-Sensor / Motion-Sensor / Microphone / Magnetic, Barcode, RFID & Smart- Card-Reader / Fingerprint-Scanner / Document-Scanner / Passport & ID Scanner / Intercom & more
Sound (Optional)	Stereo Left & Right Bi-Channel Amplified Output Multimedia Speakers
Communication Interface	Built-in> Ethernet / Wi-Fi / USB / RS-232 / RS-485 Optional> GSM (3G / 4G / 5G) / GPRS / Blue-Tooth / IR
Dimensions	For Standard (with 21.5-inch Display) Height & Width = 1599.6mm x 349mm Thickness (Depth) = 51.2mm (Top) / 178.5mm (Middle) (Dimensions for different Screen-Sizes would Vary)
Storage Temperature	-10° to 75°C
Storage Humidity	5% to 95% (non-condensing)
Operating Temperature	5°C to 45°C (Up to 65°C with built-in Air-Conditioner - Optional)
Power Supply	Supports AC 110V to 240V

