

EQ-BDx

Smart Media Player



Token No.	Counter	ABC Hospital women & children's hospital	10:25am 30-Jan-2021
T-006	2	Health & Happiness Matter	Please be seated. We will call you shortly
T-008	2		
T-007	1		
C-003	2		
C-004	2		
T-004	3		



- Multimedia Play-List
- Queue System Display
- 3rd Party Advertisements
 - Customer Information
 - In-house Promotions
 - Live Dashboard
 - Corporate Messaging
 - and more

EQ-BDx - Smart Media Player

TECHNICAL SPECIFICATIONS			
Model	EQ-BD06A	EQ-BD07A	EQ-BD09A/M
Processor	Quad-Core	Octa-Core	
RAM	1 GB		2 GB
Built-in Memory	8 GB		16 GB
Maximum Built-in Memory Capacity	Up to 64 GB	Up to 128 GB	
External HDD Support	Up to 2 TB HDD via External USB Port		
Max. Number of Units (Central Management)	Up to 65,536 under Single Control (Depending upon No. of Channels for the Central Mgmt. Software)		
Modes of Operation (Multi-Function Capability)	<ul style="list-style-type: none"> • As Main Display for Queue Management System • Multimedia Player (Can Manage Single or Multiple Playlists) • Customer Information (General / Interactive) • Notice Board & Event Management (at Main Entrance / Hotel Lobby) • Corporate Messaging (Floors / Area Wise) • In-house & 3rd Party Promotions (Videos / Pictures / Messages) • Live Dashboard (For Administrator / Operations Manager) • Quick Instructions Display (to Warehouse, Stores, etc.) and more 		
Display Proportion	16:9 / 4:3 (User Definable)		
Graphic Display	Full-HD 1920x1080 (including Mali 400 Graphic Accelerator)	Ultra HD – 4K (Including Mali 400+ Graphic Accelerator)	
Video Streaming Support	At Low Definition	At High-Definition	
Video Support Formats	H.263 / H.264 / H.265 (EQ-BD07A) / VC-1 / WMV / DV / XVID / VP6,8 / MPEG1,2,4 / RM / REAL(RMVB) / FLV / MOV / VOB / AVI / MKV / M2TS / F4V/ ASF / 3GP		
Audio Support Formats	MP3 / WMA / APE / Flac / WMA / 3GP / AAC / ADPCM / AMR / M4A / MID / OGG / PCM / WAV		
I/O Interface	HDMI / Cabled Ethernet / Wi-Fi / USB / USB-OTG Bluetooth (Optional) / 3G (Optional)		
Storage Temperature	20°C to 60°C		
Operating Temperature	5°C to 45°C		
Power Supply	5V DC 1Amp		

